



A/C REVIVER

Improves A/C Performance

NC A/C REVIVER is an air conditioning performance booster specially formulated to enhance cooling properties of new and old air conditioning and refrigeration systems by reducing mechanical friction. Ideal for use on heat pumps, split systems, mini-split units, packaged units, microchannel coils etc. **NC A/C REVIVER** contains a highly polar molecule that works synergistically with compressor oil to improve the performance of air conditioning and refrigeration systems by increasing heat transfer in the condenser and evaporator coils. The polarized molecule bonds to the metal inside the system and by removing the insulated buildup of oil forms a conductive layer to improve heat transfer. Treats systems up to 5 tons.

FEATURES & BENEFITS

- Enhances Cooling Properties of New and Old AC Systems
- Saves Energy
- Reduces Noise and Friction
- Extends Unit Working Life
- Compatible With All Refrigerants Excluding Ammonia ... and All Oils

DIRECTIONS: STEP 1. Turn the a/c system on, and verify the unit is running. Connect NC ONE & DONE A/C REVIVER Inject to the low-side service port of the system. (This is generally the large line.)

STEP 2. Ensure the valves on manifold gauge set are closed. Start by connecting the high side (red) line of manifold gauge set to the high side service port. Remove NC ONE & DONE A/C REVIVER from the Mylar bag and loosely connect the middle manifold hose (yellow) to the 1/4" SAE male fitting of the NC ONE & DONE A/C REVIVER being careful NOT to depress the Schrader core. Quickly open the high side manifold valve to purge air out of the yellow hose. Now close the high side manifold valve, and quickly tighten the yellow hose fitting to the injector.

STEP 3. Next rapidly open and close the high side valve of the manifold gauge allowing a small amount of liquid to flow through the yellow hose and NC ONE & DONE A/C REVIVER tube. With high side valve of the manifold gauge set closed, wait one minute for the yellow hose NC ONE & DONE A/C REVIVER to equalize to suction pressure. Disconnect NC ONE & DONE A/C REVIVER from suction service port and from manifold gauge set. Allow unit to run for at least 1 hour to ensure product has circulated in the system.

NC ONE & DONE A/C REVIVER NCACR
PACKAGING 6 per case

Refer to product label & Safety Data Sheet for precautionary and First Aid Information.
The SDS is available on the NRP website at www.nrproducts.com

National Refrigeration Products
985 Wheeler Way
Langhorne, PA 19047 USA - (800) 352-6951

